

29 124 GN0 **GROHTHERM SMARTCONTROL THERMOSTAT FOR CONCEALED INSTALLATION WITH 2 VALVES**








bar	1	2	3	4	5	6
—	13.9	19.6	24.0	27.7	31.0	33.9
—	15.0	21.2	26.0	30.0	33.6	36.8
—	16.7	23.7	29.0	33.5	37.4	41.0
l/min						

PRODUCT DESCRIPTION

- Colour: brushed cool sunrise
- set for final installation for
- GROHE Rapido SmartBox 35 600/35 604
- metal wall escutcheon with GROHE FastFixation (covered escutcheon and shaft sealing, covered fixing), retroactively 6° adjustable
- GROHE Long-Life finish
- GROHE SmartControl push for ON-OFF, turn for volume adjustment from GROHE Water Saving to full flow
- exchangeable symbols
- GROHE TurboStat compact cartridge with wax thermoelement
- GROHE SafeStop safety button at 38°C(calibration required)
- GROHE SafeStop Plus optional temperature limiter at 43°C or 46°C included
- built-in non return valve and dirt strainers
- multiple outlets can be run simultaneously
- without roughing-in-set
- flow performance: outlet B = 24 l/min outlet C = 26 l/min outlet B+C = 29 l/min

29 124 GN0 **GROHTHERM SMARTCONTROL THERMOSTAT FOR CONCEALED INSTALLATION WITH 2 VALVES**



bar	1	2	3	4	5	6
—	13.9	19.6	24.0	27.7	31.0	33.9
—	15.0	21.2	26.0	30.0	33.6	36.8
—	16.7	23.7	29.0	33.5	37.4	41.0
l/min						