


39 052 000 **RAPID SL ELEMENT FOR WASH BASIN, SINGLE HOLE INSTALLATION, HEIGHT ADJUSTABLE**




PRODUCT DESCRIPTION

- with noise protection
- 1.13 m finished installation height
- for on-the-wall installations or studded walls
- powder coated steel frame, self-supporting
- for dry-cladding, completely pre-assembled
- with fixed connections
- quick adjustment, lockable
- fixing material
- TÜV approved
- fixing and connecting traverse, height adjustable
- Includes wash basin fixing bolts with fixing device for ceramic
- variable distance of fixing bolts
- HT-outlet bend Ø 50 mm
- seal Ø 32 mm
- 2 noise protected fitting connections ½"
- for on-the-wall installation please order wall brackets 38 558 00M (sold separately)



39 052 000 **RAPID SL ELEMENT FOR WASH BASIN, SINGLE HOLE INSTALLATION, HEIGHT ADJUSTABLE**



SPARE PARTS, October 2012 – now

- 1: Fitting connection (Spare part-nr. 42944000)
 - 2: Elbow 2" (Spare part-nr. 42943000)
 - 3: Threaded bolt (Spare part-nr. 42247000)
 - 4: Front wall brackets (Spare part-nr. 3855800M)*
- * Optional accessories